

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
6 October 2005 (06.10.2005)

PCT

(10) International Publication Number  
**WO 2005/093300 A1**

(51) International Patent Classification<sup>7</sup>: **F16K 5/00,**  
25/00, 31/02

(21) International Application Number:  
PCT/US2005/006670

(22) International Filing Date: 2 March 2005 (02.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/550,782 5 March 2004 (05.03.2004) US

(71) Applicant (for all designated States except US): **WATERS  
INVESTMENTS LIMITED** [US/US]; 109 Lukens Drive,  
New Castle, DE 19720 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **USOWICZ, James,**

E. [US/US]; 4A Street, Douglas, MA 01516 (US).  
**CIOLKOSZ, Theodore, D.** [US/US]; 362 Adams Street,  
Milton, MA 02186 (US). **LEMELIN, Marc** [US/US]; 796  
Providence Drive, Whitinsville, MA 01588 (US).

(74) Agent: **JANIUK, Anthony, J.**; Waters Corporation, 34  
Maple Street, Milford, MA 01757 (US).


(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ,  
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,  
ZM, ZW.

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: VALVE WITH LOW FRICTION COATING

(57) Abstract: Embodiments of the present invention feature a method and device for controlling the flow of fluid. One embodiment of the device for controlling the flow of fluid comprises a rotor, stator and compression means. The rotor has a rotor fluid communication means and at least one rotor load bearing surface. The rotor load bearing surface sealably engages a stationary load bearing surface. The rotor is capable of assuming a first position and a second position by rotation. The stator has a stationary load bearing surface having stator fluid communication means. The stationary load bearing surface sealably engages the rotor load bearing surface and permits rotation of the rotor with respect to the stator. At least one of the rotor bearing surface and said stator load bearing surface has a diamond-like carbon-silica coating.



WO 2005/093300 A1



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— *with international search report*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*